

Amphenol Broadband Solutions is pleased to offer this S-Video cable. S-Video cables are used to connect to a wide variety of video devices. S-Video keeps the B/W signal and color signal separate until plugged into a four-pin device. This S-Video cable is designed to deliver a quality video signal for standard definition TV (480i). Note: If audio is required it is necessary to add a separate audio cable, such as the ASB7000 HDTV cable.



S - Video Cable

Features:

- Connectors: 4-pin DIN Male to 4-pin DIN Male
- Copper wire delivers all the detail, color and brightness you expect from your S-Video component
- Precision-made gold-plated connectors ensure long-lasting sound quality
- Fully molded connectors provide excellent strain relief
- Individually double-shielded 75-ohm coaxial conductors protect against induced noise or distortion
- Ultra-flexible PVC jacket for easy installation
- Connects digital camcorders, satellite receivers, DVD players, PC with TV out or any video source with S-Video output jacks to television, monitor or A/V receiver with S-Video input jacks
- Custom lengths available
- Shorter lengths are for stacked equipment installations

Specifications				
Jacket	PVC 4.0mm outside diameter			
Braiding	Copper clad steel (CCS) 28 members @ 0.1 mm			
Shielding	Spiral braid			
Conductor	26AWG 7/0.16			
Insulation	0.51mm PVC			
Connector	Copper / Gold Plated			

Part	Number	Description	Application	Length
ASE	31700-06	S-Video Cable	Video Only	6 Foot
ASE	31700-10	S-Video Cable	Video Only	10 Foot
ASE	31700-12	S-Video Cable	Video Only	12 Foot