


625 Series Coaxial Cable
 Copper Clad Aluminum Conductor
 Foamed Polyethylene Dielectric
 Seamless Aluminum Tube Outer Conductor
 Medium Density Polyethylene Jacket



Cable Ordering Information

Part Number	Description	NEC / CE Listing
750625J000BK00100001	T10625J	

Characteristics

Material	Detail	inches	mm
Inner Conductor	Copper Clad Aluminum	0.136	3.45
Dielectric	Foamed Polyethylene	0.563	14.3
Outer Conductor	Seamless Aluminum Tube	0.625	15.9
Floodant	---	---	---
Jacket	Polyethylene, Outdoor, Black	0.685	17.4
Messenger	---	---	---
Cable Width	---	---	---
	---	---	---
	---	---	---

Mechanical Specifications

Minimum Bend Radius, in. (mm)		4.5	(114)
Product Weight	(less reel)	145	(216)

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t10625j_3.0ghz19.docx
 Revision: 2019-09-03
 Page: 1 of 2

Amphenol Broadband Solutions.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Toll +1-434-432-1800
 Fax +1-434-432-1821
 www.timesfiber.com

uncontrolled copy
 All Rights Reserved,
 Specifications subject to change without notice



Electrical Specifications

Impedance, Ω	75 \pm 2	
Velocity of Propagation, %	87	
Capacitance, Nominal	15.3 pF/ft	50.2 pF/m
DC Resistance	Ω / kft	Ω / km
Inner Conductor	0.86	2.82
Outer Conductor	0.23	0.75
Loop	1.09	3.57

Attenuation, Maximum @ 68 °F (20 °C)

Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.13	0.43
55	0.45	1.48
85	0.56	1.84
211	0.89	2.92
250	0.98	3.22
270	1.02	3.35
300	1.08	3.54
330	1.14	3.74
350	1.18	3.87
400	1.27	4.17
450	1.35	4.43
500	1.43	4.69
550	1.51	4.95
600	1.58	5.18
750	1.78	5.84
870	1.95	6.40
1002	2.07	6.79
1100	2.19	7.19
1200	2.30	7.55
1218	2.32	7.61
1300	2.40	7.87
1400	2.50	8.20
1625	2.61	8.56
1600	2.70	8.86
1700	2.80	9.19
1794	2.89	9.48
1800	2.90	9.51
2000	3.07	10.07
2200	3.25	10.66
2400	3.41	11.19
2600	3.58	11.75
2800	3.74	12.27
3000	3.89	12.76

Structural Return Loss

MHz		dB
	5-1002	-30

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t10625j_3.0ghz19.docx
Revision: 2019-09-03
Page: 2 of 2

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice

Amphenol Broadband Solutions.
358 Hall Avenue
Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com