

## MoCA Broadband Digital Splitters Vertical True Flex™ and Horizontal Model ABS200H/VF

### MoCA Broadband Digital Splitter Series

#### Description:

MoCA is rapidly becoming the home networking standard for delivering HD and data signals over existing coaxial cables. Guarantee your MoCA network runs smoothly with Extreme Broadband's integrated MoCA splitters that are precisely designed to boost signal strength at higher frequencies and maximum bandwidth. A simple way to improve MoCA network integrity and system reliability. Designed to the highest technical specifications as the traditional Extreme Broadband Splitter line, the MoCA Splitter is another option for MoCA.



#### Features & Benefits:

- 1675 GHz performance
- Available in Vertical True Flex™ or Horizontal Housings
- Built to SCTE standards
- Capacitive coupled F-ports prevent hum modulation
- UL Listed
- Machined F-ports pressure sealed
- Zinc die cast housing and back cover
- Soldered back for EMI shield effectiveness

#### Applications:

Premise, Multi-Dwelling Units (MDU) and Business.

## Additional Info:

### Specifications

Insertion Loss	Frequency (MHz)	ABS202H/VF	ABS203H/VF	ABS203HB/VFB	ABS204H/VF	ABS208H/VF
dB Max	5 - 400	3.5	3.5/7.0	5.5	7.0	10.5
	401 - 600	3.7	3.7/7.3	5.5	7.3	11.0
	601 - 1002	3.9	3.9/7.7	5.9	7.7	11.5
	1125 - 1675	6.0	6.0/11.0	8.0	11.0	17.0
<b>Isolation</b>						
dB Min	5 - 10	27	27/30	30	30	25
	11 - 85	35	40/36	36	36	30
	86 - 870	25	32/25	25	25	25
	871 - 1002	23	23/22	22	22	23
Adjacent	1125 - 1675	<25	<25	<25	<25	<25 (adjacent 1-2)
Non-Adjacent	1125 - 1675	N/A	<30	<30	<30	<30 (non-adjacent 1-4)
Cross	1125 - 1675	N/A	N/A	N/A	N/A	35 (cross 1-8))
<b>Return Loss (Output/Input)</b>						
dB Min	5 - 10	20	20	20	20	20
	11 - 85	27	27	27	24.5	20
	86 - 870	22	22	22	20	20
	871 - 1002	20	20	20	20	20
	1125 - 1675	Not yet characterized				
<b>RFI</b>						
	5 - 1675	130	130	130	130	130
<b>Bonding Mechanism</b>						
UL Listed						
<b>Surge Protection</b>						
Input	6kV/3KA Combo Wave					
Output	6kV/200A Ring Wave					
<b>Second Harmonic</b>						
--40dBmV, after 6kV combo/ring surge Measuring with a 60-dBmV return input carrier						

Specifications Are Subject To Change Without Notice  
 © 2005-2008 Extreme Broadband Engineering LLC. All rights reserved.  
 Extreme Broadband Engineering is a registered trademark. Infinity Premise™ is a trade of Extreme Broadband Engineering.

Customers are reminded they are SOLELY responsible for confirming that all products are properly installed and used in accordance with codes and regulations.