


875 Series Coaxial Cable  
Copper Clad Aluminum Conductor  
Foamed Polyethylene Dielectric  
Seamless Aluminum Tube Outer Conductor  
Medium Density Polyethylene Jacket  
0.250" Galvanized Steel Messenger



**Cable Ordering Information**

Part Number	Description	NEC / CSA Listing
750875MS00BK13000001	T10875MS / 250 MESS	n/a

**Characteristics**

Material	Detail	inches	mm
Inner Conductor	Copper Clad Aluminum	0.194	4.93
Dielectric	Foamed Polyethylene	0.797	20.2
Outer Conductor	Seamless Aluminum Tube	0.875	22.2
Floodant	---	---	---
Jacket	Polyethylene, Outdoor, Black	0.945	24.0
Messenger	Galvanized Steel	0.250	
Cable Width	---	1.440	

**Mechanical Specifications**

Minimum Bend Radius, in. (mm)		8.0	( 203)
Product Weight, lbs/kft (kg/km)	(less reel)	442	( 658)

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t10875ms - 250 mess\_1.8ghz17  
Revision: 11.2.2017  
Page: 1 of 2

Amphenol Broadband Solutions  
358 Hall Avenue  
Wallingford, CT 06492  
Toll Free +1-800-677-2288  
Toll +1-434-432-1800  
Fax +1-434-432-1821  
www.timesfiber.com

**uncontrolled copy**

All Rights Reserved,  
Specifications subject to change without notice

Electrical Specifications		
Impedance, $\Omega$	75 $\pm$ 2	
Velocity of Propagation, %	87	
Capacitance, Nominal	15.3 pF/ft	50.2 pF/m
DC Resistance	$\Omega$ / kft	$\Omega$ / km
Inner Conductor	0.42	1.38
Outer Conductor	0.13	0.43
Loop	0.55	1.81
Structural Return Loss, minimum	dB	
5~1002 MHz	30	

Attenuation, Maximum @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.09	0.30
55	0.32	1.05
211	0.64	2.09
250	0.70	2.31
270	0.73	2.40
300	0.78	2.56
330	0.82	2.69
350	0.84	2.76
400	0.91	2.99
450	0.97	3.18
500	1.03	3.38
550	1.09	3.58
600	1.14	3.74
750	1.29	4.23
870	1.41	4.63
1000	1.53	5.02
1100	1.61	5.28
1200	1.69	5.54
1218	1.70	5.58
1300	1.76	5.77
1400	1.84	6.04
1500	1.93	6.33
1600	2.00	6.56
1700	2.05	6.73
1794	2.12	6.96
1800	2.13	6.99

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t10875ms - 250 mess\_1.8ghz17  
Revision: 11.2.2017  
Page: 2 of 2

Amphenol Broadband Solutions  
358 Hall Avenue  
Wallingford, CT 06492  
Toll Free +1-800-677-2288  
Toll +1-434-432-1800  
Fax +1-434-432-1821  
www.timesfiber.com

**uncontrolled copy**

All Rights Reserved,  
Specifications subject to change without notice