


Series 11 Coaxial Cable
Copper Clad Steel Conductor
Foamed Polyethylene Dielectric
Bonded APA Laminate Shield
60% Aluminum Braid
APA Laminate Shield
40% Aluminum Braid
Underground Floodant
Black Polyethylene Jacket



Cable Ordering Information

Part Number	Description	NEC / CSA Listing
011Q64E00BK0610000R1	T11Q60/40-FE Black	None

Characteristics

Material	Detail	inches	mm
Inner Conductor	Copper Clad Steel	0.0641	1.63
Dielectric	Foamed Polyethylene	0.280	7.11
1 st Outer Conductor	Sealed APA Tape	0.288	7.32
2 nd Outer Conductor	60% Aluminum Braid	0.312	7.92
3 rd Outer Conductor	APA Tape	0.316	8.03
4 th Outer Conductor	40% Aluminum Braid	0.341	8.66
Floodant	Underground	---	---
Jacket	Polyethylene, Black	0.407	10.3
Twisted Pairs	---	---	---
Messenger	---	---	---

Mechanical Specifications

Minimum Bend Radius, in. (mm)		1.5	(38.10)
Product Weight	(less reel)	53 lbs /kft	

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Amphenol Broadband Solutions
358 Hall Avenue
Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com

Document: t11q6040-fe black_1.8ghz18.docx
Revision: 12.19.2018
Page: 1 of 2

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice

Electrical Specifications		
Impedance, Ω	75 \pm 3	
Velocity of Propagation, %	85	
Capacitance, Nominal	16.2 pF/ft	53.2 pF/m
DC Resistance	Ω / kft	Ω / km
Inner Conductor	12.3	40
Outer Conductor	4.40	14
Loop	16.7	54

Attenuation, Maximum @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.38	1.25
55	0.96	3.15
211	1.90	6.23
250	2.05	6.73
270	2.13	6.99
300	2.25	7.38
330	2.35	7.71
350	2.42	7.94
400	2.60	8.53
450	2.75	9.02
500	2.90	9.51
550	3.04	9.97
600	3.18	10.43
750	3.65	11.98
870	4.06	13.32
1000	4.35	14.27
1100	4.54	14.90
1200	4.71	15.45
1218	4.92	16.14
1300	4.96	16.27
1400	5.14	16.86
1500	5.45	17.88
1600	5.66	18.57
1700	5.86	19.23
1794	5.99	19.65
1800	6.04	19.82

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t11q6040-fe black_1.8ghz18.docx
Revision: 12.19.2018
Page: 2 of 2

Amphenol Broadband Solutions
358 Hall Avenue
Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice