


Series 59 Coaxial Cable  
Silver-Plated Copper Clad Steel Conductor  
Foamed Polyethylene Dielectric  
Bonded APA Laminate Shield  
95% Aluminum Braid  
APA Laminate Shield – Short-Fold  
Color PVC Jacket  
NEC/CEC 800 CM NEC 820 CATV Listed  
Headend Application – 08X Bundle  
Color PVC Outer Jacket



Coax Jacket Colors Available

Black	White	Gray	Red	Blue
Violet	Orange	Brown	Green	Yellow
Aqua	Rose	Neutral	Pink	

**Cable Ordering Information**

Part Number	Description	NEC / CSA Listing
059G95V29xx9190000R1	T59SCSTSF95-V(CMR-CMG) xxxx-xxxx / HE 08X UNIT	NEC/CEC 800 CM – NEC 820 Listed

**Characteristics**

Material	Detail	inches	mm
Inner Conductor	Silver-Plated Copper Clad Steel	0.0320	0.81
Dielectric	Foamed Polyethylene	0.144	3.66
1 <sup>st</sup> Outer Conductor	Sealed APA Tape	0.152	3.86
2 <sup>nd</sup> Outer Conductor	95% Aluminum Braid	0.176	4.47
3 <sup>rd</sup> Outer Conductor	APA Tape – Short Fold	0.180	4.57
4 <sup>th</sup> Outer Conductor	---	---	---
Floodant	---	---	---
Jacket	PVC, FR TYP(2), Color	0.242	6.15
Bundle Diameter	---	---	---

**Mechanical Specifications**

Minimum Bend Radius, in. (mm)		10.0	( 254)
Product Weight	(less reel)	37 lbs /kft	

xx & xxxx-xxxx = denotes inner and outer jacket color, other available with conditions

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Times Fiber Communications, Inc.  
358 Hall Avenue  
Wallingford, CT 06492  
Toll Free +1-800-677-2288  
Toll +1-434-432-1800  
Fax +1-434-432-1821  
www.timesfiber.com

Document: t59scstsf95-v (cm-catv) xxxx-xxxx he 08x\_1.8ghz19.docx  
Revision: 1.17.2019  
Page: 1 of 2

**uncontrolled copy**

All Rights Reserved,  
Specifications subject to change without notice

Electrical Specifications		
Impedance, $\Omega$	75 $\pm$ 3	
Velocity of Propagation, %	85	
Capacitance, Nominal	16.2 pF/ft	53.2 pF/m
DC Resistance	$\Omega$ / kft	$\Omega$ / km
Inner Conductor	25.30	83
Outer Conductor	4.50	15
Loop	29.8	98

Attenuation, Maximum @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.86	2.82
55	2.05	6.73
211	3.80	12.47
250	4.10	13.45
270	4.22	13.85
300	4.45	14.60
330	4.66	15.29
350	4.80	15.75
400	5.10	16.73
450	5.40	17.72
500	5.70	18.70
550	5.95	19.52
600	6.20	20.34
750	6.97	22.87
870	7.57	24.84
1000	8.12	26.64
1100	8.52	27.95
1200	8.91	29.23
1218	8.99	29.49
1300	9.29	30.48
1400	9.64	31.63
1500	10.05	32.97
1600	10.41	34.15
1700	10.76	35.30
1794	11.06	36.29
1800	11.08	36.35

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t59scstsf95-v (cm-catv) xxxx-xxxx he 08x\_1.8ghz19.docx  
Revision: 1.17.2019  
Page: 2 of 2

Times Fiber Communications, Inc.  
358 Hall Avenue  
Wallingford, CT 06492  
Toll Free +1-800-677-2288  
Toll +1-434-432-1800  
Fax +1-434-432-1821  
www.timesfiber.com

**uncontrolled copy**

All Rights Reserved,  
Specifications subject to change without notice