


ABS Coaxial Cable Product
Type: T6TSFx77-LTV (AA) Black -
051M / T-GNGN



Series 6 Coaxial Cable
Copper Clad Steel Conductor
Foamed Polyethylene Dielectric
Bonded APA Laminate Shield
77% Aluminum Braid
Moisture Inhibiting lifeTime®
APA Laminate Shield (ShieldX®)
Black PVC Jacket w/ Rodent Repel™
2 Green Tracer Stripes
0.051" Galvanized Steel Messenger



Designed for enhanced shielding, targeting today's LTE interference problems...

Cable Ordering Information

Part Number	Description	NEC / CSA Listing
006277V84BK6540000R1	T6TSFx77-LTV (AA) Black -051M / T-GNGN	None

Characteristics

Material	Detail	inches	mm
Inner Conductor	Copper Clad Steel	0.0403	1.02
Dielectric	Foamed Polyethylene	0.180	4.57
1 st Outer Conductor	Sealed APA Tape	0.188	4.78
2 nd Outer Conductor	77% Aluminum Braid	0.212	5.38
3 rd Outer Conductor	APA Tape (ShieldX®)	0.216	5.49
Floodant	Moisture Inhibiting lifeTime®	---	---
Jacket	PVC, Outdoor Grade, Black	0.278	7.06
Twisted Pairs	---	---	---
Messenger	Galvanized Steel	0.051	1.30

Mechanical Specifications

Minimum Bend Radius, in. (mm)		1.0	(25.40)
Product Weight	(less reel)	42 lbs /kft	

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t6tsfx77-ltv aa gngn black -051m_1.8ghz18.docx

Revision: 12.12.2018
Page: 1 of 2

Amphenol Broadband Solutions
358 Hall Avenue
Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice

ABS Coaxial Cable Product

Type: T6TSFx77-LTV (AA) Black - 051M / T-GNGN



Electrical Specifications		
Impedance, Ω	75 \pm 3	
Velocity of Propagation, %	85	
Capacitance, Nominal	16.2 pF/ft	53.2 pF/m
DC Resistance	Ω / kft	Ω / km
Inner Conductor	31.0	102
Outer Conductor	5.70	19
Loop	36.7	120

Attenuation, Maximum @ 68 °F (20 °C)		
Frequency, MHz	dB / 100 ft	dB / 100 m
5	0.58	1.90
55	1.60	5.25
211	3.05	10.01
250	3.30	10.83
270	3.37	11.06
300	3.55	11.65
330	3.74	12.27
350	3.85	12.63
400	4.15	13.62
450	4.40	14.44
500	4.66	15.29
550	4.90	16.08
600	5.10	16.73
750	5.65	18.54
870	6.11	20.05
1000	6.55	21.49
1100	6.87	22.54
1200	7.18	23.56
1218	7.21	23.65
1300	7.47	24.51
1400	7.75	25.43
1500	8.06	26.44
1600	8.34	27.36
1700	8.61	28.25
1794	8.85	29.04
1800	8.87	29.10

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t6tsfx77-ltv aa gngn black -051m_1.8ghz18.docx

Revision: 12.12.2018
Page: 2 of 2

uncontrolled copy

All Rights Reserved,
Specifications subject to change without notice

Amphenol Broadband Solutions
358 Hall Avenue
Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com